

8770 Non-Paired - Audio, Control and Instrumentation Cable

	<p>For more information please call 1-800-Belden1</p> <p><u>See Put-ups and Colors</u></p>
---	--

Description:

18 AWG stranded (16x30) tinned copper conductors, conductors cabled, polyethylene insulation, overall Beldfoil® aluminum-polyester shield (100% coverage), 20 AWG stranded tinned copper drain wire, PVC jacket.

PHYSICAL CHARACTERISTICS:

CONDUCTOR:

Number of Conductors	3
Total Number of Conductors	3
AWG	18
Stranding	16x30
Conductor Material	TC - Tinned Copper

INSULATION:

Insulation Material	PE - Polyethylene
Nom. Insulation Wall Thickness	.018 in.

OVERALL CABLING:

Overall Cabling Lay Length	1.5 in.
Overall Cabling Twists/ft.	8

Overall Cabling Color Code Chart :

Number	Color
1	Black
2	Red
3	Clear

OUTER SHIELD:

Outer Shield Material Trade Name	Beldfoil®
Outer Shield Type	Tape
Outer Shield Material	Aluminum Foil-Polyester Tape w/Shorting Fold
Outer Shield % Coverage	100 %

OUTER SHIELD DRAIN WIRE :

Outer Shield Drain Wire AWG	20
Outer Shield Drain Wire Stranding	Stranded
Outer Shield Drain Wire Conductor Material	TC - Tinned Copper

OUTER JACKET:

8770 Non-Paired - Audio, Control and Instrumentation Cable

Outer Jacket Material	PVC - Polyvinyl Chloride
Outer Jacket Nominal Wall Thickness	.033 in.

OVERALL NOMINAL DIAMETER:

Overall Nominal Diameter	.246 in.
--------------------------	----------

MECHANICAL CHARACTERISTICS:

Operating Temperature Range	-20°C To +60°C
UL Temperature Rating	60°C (UL AWM Style 2093)
Bulk Cable Weight	36.2 lbs/1000 ft.
Max. Recommended Pulling Tension	74 lbs.
Min. Bend Radius (Install)	2.5 in.

APPLICABLE SPECIFICATIONS AND AGENCY COMPLIANCE:

APPLICABLE STANDARDS:

NEC/(UL) Specification	CM
CEC/C(UL) Specification	CM
AWM Specification	2093 (300 V 60°C)

FLAME TEST:

UL Flame Test	UL1581 Vertical Tray
---------------	----------------------

PLENUM/NON-PLENUM:

Plenum (Y/N)	N
Plenum Number	88770

ELECTRICAL CHARACTERISTICS:

Nom. Characteristic Impedance	69 Ohms
Nom. Inductance	.1844 µH/ft
Nom. Capacitance Conductor to Conductor @ 1 KHz	24 pF/ft
Nom. Cap. Cond. to Other Cond. & Shield @ 1 KHz	48 pF/ft
Nom. Conductor DC Resistance @ 20 Deg. C	6.6 Ohms/1000 ft
Nominal Outer Shield DC Resistance @ 20 Deg. C	8.5 Ohms/1000 ft
Max. Operating Voltage - UL	300 V RMS (UL AWM Style 2093)
Other Maximum Continuous Currents	5.3 Amps per conductor @ 25°C

PUT-UPS AND COLORS:

Item	Description	Put-Up (ft.)	Ship Weight (lbs.)	Jacket Color	Notes
8770 0601000	3 #18 LDPE FS PVC	1000	40	CHROME	C
8770 06010000	3 #18 LDPE FS PVC	10000	430	CHROME	C Y
8770 060500	3 #18 LDPE FS PVC	500	20.5	CHROME	



8770 Non-Paired - Audio, Control and Instrumentation Cable

8770 060U1000	3 #18 LDPE FS PVC	U1000	39	CHROME	
8770 060U500	3 #18 LDPE FS PVC	U500	20	CHROME	

C = CRATE REEL PUT-UP.

Y = FINAL PUT-UP LENGTH MAY VARY -10% TO +20% FROM LENGTH SHOWN. MAY CONTAIN 2 PIECES. MINIMUM LENGTH OF ANY ONE PIECE IS 1500'.

Revision Number: 2 Revision Date: 11-10-2003

© 2003 Belden Wire & Cable Company
All Rights Reserved.

Although Belden Electronics Division ("Belden") makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.