

9116 Coax - Broadband Coax CATV Cable



Description:

18 AWG solid .040" bare copper-covered steel conductor, gas-injected foam polyethylene insulation, Duobond® II and a 60% aluminum braid shield, PVC jacket.

PHYSICAL CHARACTERISTICS:

CONDUCTOR:

Number of Coax	1
Total Number of Conductors	1
Series Type	Series 6
AWG	18
Stranding	Solid
Conductor Diameter	.040 in.
Conductor Material	BCCS - Bare Copper Covered Steel

INSULATION:

Insulation Material	Gas-injected FPE - Foam Polyethylene
Insulation Diameter	.180 in.

OUTER SHIELD:

Outer Shield Material Trade Name	Duobond® II
Outer Shield Type	Tape/Braid

Outer Shield Material :

Layer Number	Trade Name	Type	Material	% Coverage (%)
1	Bonded Duofoil®	Tape	Bonded Aluminum Foil-Polyester Tape-Aluminum Foil	100
2		Braid	AL - Aluminum	60

Outer Shield % Coverage	100 %
-------------------------	-------

OUTER JACKET:

Outer Jacket Material	PVC - Polyvinyl Chloride
-----------------------	--------------------------

OVERALL NOMINAL DIAMETER:

Overall Nominal Diameter	.270 in.
--------------------------	----------

MECHANICAL CHARACTERISTICS:

Operating Temperature Range	-40°C To +80°C
-----------------------------	----------------



9116 Coax - Broadband Coax CATV Cable

Bulk Cable Weight	30 lbs/1000 ft.
Max. Recommended Pulling Tension	126 lbs.
Min. Bend Radius (Install)	3 in.

APPLICABLE SPECIFICATIONS AND AGENCY COMPLIANCE:

APPLICABLE STANDARDS:

NEC/(UL) Specification	CATV, CM
CEC/C(UL) Specification	CM

FLAME TEST:

UL Flame Test	UL1581 Vertical Tray
---------------	----------------------

PLENUM/NON-PLENUM:

Plenum (Y/N)	N
Plenum Number	9116P

ELECTRICAL CHARACTERISTICS:

Nom. Characteristic Impedance	75 +/-3 Ohms
Nom. Inductance	.097 µH/ft
Nom. Capacitance Conductor to Shield	16.2 pF/ft
Nominal Velocity of Propagation	83 %
Nominal Delay	1.2 ns/ft
Nom. Conductor DC Resistance @ 20 Deg. C	28 Ohms/1000 ft
Nominal Outer Shield DC Resistance	9 Ohms/1000 ft

Minimum Structural Return Loss :

Description	Frequency (MHz)	Start Frequency (MHz)	Stop Frequency (MHz)	Minimum Structural Return Loss (dB)
		5	1000	20

Max. Attenuation :

Description	Frequency (MHz)	Start Frequency (MHz)	Stop Frequency (MHz)	Max. Attenuation (dB/100 ft.)
	5			0.67
	55			1.60
	211			2.87
	270			3.24
	300			3.43
	350			3.72
	400			4.00
	450			4.26
	550			4.71
	750			5.59
	870			6.00
	1000			6.54

Max. Operating Voltage - UL	350 V RMS
-----------------------------	-----------

NOTES:



9116 Coax - Broadband Coax CATV Cable

Notes Sweep tested 5 MHz to 1 GHz

PUT-UPS AND COLORS:

Item	Description	Put-Up (ft.)	Ship Weight (lbs.)	Jacket Color	Notes
9116 0091000	#18 GIFHDL DPE SH PVC	1000	31	WHITE	
9116 009500	#18 GIFHDL DPE SH PVC	500	15.5	WHITE	
9116 009U1000	#18 GIFHDL DPE SH PVC	U1000	30	WHITE	
9116 009U500	#18 GIFHDL DPE SH PVC	U500	15.5	WHITE	
9116 0101000	#18 GIFHDL DPE SH PVC	1000	31	BLACK	C
9116 010500	#18 GIFHDL DPE SH PVC	500	17.5	BLACK	
9116 010S700	#18 GIFHDL DPE SH PVC	S700	18.9	BLACK	
9116 010U1000	#18 GIFHDL DPE SH PVC	U1000	31	BLACK	
9116 010U500	#18 GIFHDL DPE SH PVC	U500	17.5	BLACK	
9116 290U1000	#18 GIFHDL DPE SH PVC	U1000	31	BEIGE, LIGHT	
9116 Q5H1000	#18 GIFHDL DPE SH PVC	1000	31	WHITE, NEUTRAL	
9116 Q5HU1000	#18 GIFHDL DPE SH PVC	U1000	30	WHITE, NEUTRAL	

C = CRATE REEL PUT-UP.

Revision Number: 1 Revision Date: 12-29-2003

© 2003 Belden Wire & Cable Company
All Rights Reserved.

Although Belden Electronics Division ("Belden") makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.